11th STREET

LINDEN ST

S. MAIN STREET

N

ALL WATER SERVICES ARE 1¼" POLYETHYLENE UNLESS SHOWN OTHERWISE

CONTRACTOR TO VERIFY LINE AND ELEVATION OF ALL EXISTING PIPES AT CONNECTING POINTS PRIOR TO INSTALLING STORM, SANITARY, AND WATER LINES

444 MAIN ST.

Kwik Trip Carwash

SANITARY LATERAL CONNECTED ON MAIN ST

445 LINDEN ST

SANITARY LATERAL CONNECTED ON LINDEN ST

15

22

18

456 MAIN ST.

SANITARY LATERAL CONNECTED ON MAIN ST

Kwik Trip

EX TYPE "A" CB
STA: 0+99.19 30.65' L
RIM 764.99
12" SE OUT 761.01

ABANDON & SEAL CB
EX TYPE "H" CB
STA: 1+52.65 18.44' L
RIM 764.62
12" S OUT 761.30
4" NE IN 762.62

PROP TYPE "H" CB 200-N
STA: 1+59.53 16.00' L
RIM 764.69
12" S OUT 761.67
4" N IN 762.62

EX ST MH
STA: 1+23.52 5.11' L
RIM 765.47

EX "OG" CB
STA: 2+82.08 38.36' L
RIM 765.00
6" E IN 762.92
6" S OUT 762.90

CONNECT TO EX 8"x6" TEE & PROP 32# ANODE BAG
STA: 3+89.6, 16.2' R

ABANDON WATER VALVE

PROP 8" CONCRETE PAVEMENTWITH 5" 1-1/4" BASE

1+58.03 36.0' L
19' BC RADIUS

VERIFY STM LATERAL LOCATION & DEPTH

PROP 30 LF 12" CL III RCP ST SWR @ 1.00%

ST CB 200-N
RIM 764.69

ST CB 200-S
RIM 764.73

PROP 2 LF 15" CL III RCP ST SWR @ 2.08%

SAN MH ADJUST CASTING RIM 765.41

EX METER

REMOVE, SALVAGE AND RELOCATE EX. METER PED

SALVAGE EXIST. STONE

1+51.63 36.0' R
19' BC RADIUS

PROP TEMP BLOW OFF LOCATION TO BE DETERMINED

CONNECT TO EX 8" TEE & PROP 32# ANODE BAG
STA: 1+30.6, 11.9' R

EX 16" C.I. WATER

EX 8" D.I. WATER

EX 4" C.I. WATER

EX 48" RCP ST

EX 8" PVC SAN

EX 15" RCP ST

EX 12" RCP ST

EX 8" D.I. WM

EX 6" PVC ST

EX 6" HDPE ST

SAW CUT

75'

66'

54'

120'

50'

56'

131.8'

125'

123.5

101+00

102+00

1+00

2+00

3+00

4+00